

TATSUMI MARINE CO.,LTD.

3RD FLOOR, TATSUMI BLDG.
 3-8-7 IIDABASHI CHIYODAKU,TOKYO 102-0072, JAPAN
 Phone : 03-3265-5215/5216/5217 (Business Dept)
 Fax : 03-3265-5315



M/T " SOUTHERN LION "

Type : OIL / CHEMICAL TANKER
 Owner : SOUTHERN CHEMICAL CARRIERS S.A.
 Operator : TATSUMI MARINE CO., LTD.
 Built : AUGUST, 2011
 Builder : SHITANOE SHIPBUILDING CO., LTD. S-NO : 1292
 Nationality : PANAMA
 IMO Number : 9567752
 Call Sign : 3FBG9
 Inmarsat C Telex : 437111510
 Inmarsat F Phone : +870-7731-91759
 Inmarsat F Fax : +870-7831-95759
 Japan Local Phone : 090-3022-5967
 Japan Local Fax : NONE
 E-Mail : southernlion@jrcmail.com
 Length (O.A.) : 126.50M
 Length (B.P.) : 118.42M
 Breadth : 20.30M
 Depth : 11.50M
 Draft : 8.859 M (SUMMER)
 Dead Weight : 12,651.34MT
 Gross Tonnage : 7,424.00T
 Net Tonnage : 3,962.00T
 Class : NK: NS* (Tanker, Oils-Flashpoint on and below 60°C and Chemicals Type II & III) (ESP), MNS*
 Engine : B&W 6S35MC MK-7 (HITACHI make) (4,440 KW (6,060PS))
 Speed : 14.00 KNOTS
 Crew : MAX 22 PERSONS
 Bow thruster : 629PS

Cargo Tanks
 (Capacity : M³)

	PORT	STBD.
*No.1	351.557	351.562
No.2	663.507	663.509
*No.3	1,320.775	1,320.780
No.4	1,297.113	1,297.115
*No.5	1,366.254	1,366.259
No.6	1,278.144	1,278.146
*No.7	734.164	734.169
TOTAL	7,011.514	7,011.540
G.TOTAL	14,023.054	

(Slop tank : 7S)

Material of Cargo Tank : Stainless Steel 316L for all cargo tank
 Designed Cargo Tank Specific Gravity : 1.9 tons/m3 for No.1,No.7 and 1.5 tons/m3 for other tank
 Acid Cargo Stowage : 1PS/3PS/5PS/7PS
 Submerged Cargo Pump : 200m3/h x 80m/TH x 2 Set (1PS) (Carpenter20)
 : 300m3/h x 80m/TH x 12 Set (3,,5, 7 PS) (Carpenter20)
 : 300m3/h x 80m/TH x 12 Set (2, 4, 6PS) (SUS316L)
 Portable cargo Pump : 70m3/h x 70m/TH x 1 Set (SUS316)
 Cargo Manifold : Common Line Manifold JIS 10inch Independent Manifold JIS-6 inch
 Heating System : All tank (SUS316L Heating Coil) by Steam

Cargo Hose Crane : SWL 5 Ton
 Forecastle Deck Chain Mooring Bracket : 1-Set (SWL-1059KN or 107.9KT) Type : JIS-F-2029-1978-52