

TATSUMI MARINE CO.,LTD.

3RD FLOOR, TATSUMI BLDG.
3-8-7 IIDABASHI CHIYODAKU,TOKYO 102-0072, JAPAN
Phone : 03-3265-5215/5216/5217 (Business Dept)
Fax : 03-3265-5315



M/T " SOUTHERN OWL "

Type : OIL / CHEMICAL TANKER
Owner : SOUTHERN CHEMICAL CARRIERS S.A.
Built : FEB., 2016 AT IMABARI,JAPAN
Builder : ASAKAWA SHIPBUILDING CO., LTD. S-NO : 612
IMO No. : 9773143
Nationality : LIBERIA
Call Sign : D5K18
Inmarsat : PHONE 870-773193345
: FAX 870-783197345
E-Mail : southernowl@jrcmail.com
Length (O.A.) : 156.53 M
Length (P.P.) : 149.00 m
Breadth : 25.00 m
Depth : 14.00 m
Draft(Summer) : 10.613 m
Dead Weight : 26,057MT
Gross Tonnage : 14,965T
Net Tonnage : 8,108T
Class : Nippon Kaiji Kyokai NS *(Tanker, Oils-Flashpoint on and below 60°C and Chemicals Type II and III, PSPC-WBT) (ESP) (IWS)(IHM)
Main Engine : 6S46ME-B8.3
Speed : 15.0 KNOTS
Crew : MAX 25 PERSONS
Bow Thruster : 938bhp

Cargo Tanks

No.	Capacity (98%) M3
NO.1W	2,130.605
NO.2W	2,659.648
NO.3W	1,277.045
NO.4W	2,992.541
NO.5W	1,279.013
NO.6W	2,662.314
NO.7W	1,278.319
NO.8W	2,662.789
NO.9W	1,278.674
NO.10W	2,995.816
NO.11W	1,278.529
NO.12W	2,662.457
NO.13W	1,945.436
TOTAL	27,103.186
G.TOTAL	—

(Slop tank : 13PS)

Material of Cargo Tank : Stainless Steel 316L for all cargo tank
Designed Cargo Tank Specific Gravity : 1.50 tons/M3 for all tanks
Cargo Tank : 1PS/2PS/4PS/6PS/8PS/10PS/12PS/13PS

Submerged Cargo Pump : 300m³/h X 0.78MPa X 16 sets
(Carpenter20/SUS316L)
: 300m³/h X 0.78MPa X 10 sets (SUS316L)

Portable cargo Pump : 70m³/h X 0.69MPa x 1 set (SUS316)
Cargo Manifold : Common Line Manifold JIS 10inch
Independent Manifold JIS-6 inch

Heating System : All tanks (SUS316L/Heating Coil) Steam

Hose Handling Crane : Hydraulic type 10 Ton