

# TATSUMI MARINE CO.,LTD.

3RD FLOOR, TATSUMI BLDG.  
 3-8-7 IIDABASHI CHIYODAKU, TOKYO 102-0072, JAPAN  
 Phone : 03-3265-5215/5216/5217 (Business Dept)  
 Fax : 03-3265-5315



## M/T " SOUTHERN TURKEY "

Type : OIL/CHEMICAL TANKER  
 Owner : SOUTHERN DRAGON CHEMICAL S.A.  
 Operator : TATSUMI MARINE CO., LTD.  
 Built : 26th MARCH, 2018  
 Builder : SHITANOE SHIPBUILDING CO., LTD. S-NO : 1343  
 Nationality : LIBERIA  
 IMO Number : 9749740  
 Call Sign : D5QB4  
 Inmarsat FBB Phone : 010-870-7732-46652  
 Inmarsat FBB Fax : 010-870-7830-12296  
 MMSI : 636018519  
 E-Mail : southernturkey@jrcmail.com  
 Inmarsat C E-Mail : 463724753@satmailc.com  
 Length (O.A.) : 134.99M  
 Length (B.P.) : 129.00M  
 Breadth : 23.20M  
 Depth : 12.72M  
 Draft : 9.465 M (SUMMER)  
 Dead Weight : 17,300.93 MT  
 Gross Tonnage : 9,997 TONS  
 Net Tonnage : 5,647 TONS  
 Class : Class NK(No.180931) : NS\* (Tanker, Oils-Flashpoint on and below 60°C and Chemicals Type II & III, Performance Standard for Protective Coatings for Dedicated Seawater Ballast Tanks in All Types of Ships and Double-side Skin Spaces of Bulk Carriers) (ESP)(IWS)(IHM) MNS\*

Engine : HITACHI-MAN B&W 6S40ME-B9.3 2cyc. Crosshead type diesel engine  
 4,620 KW X 124min-1 X 1 Set  
 Speed : 14.00 KNOTS  
 Crew : MAX 24 PERSONS  
 Bow thruster : 695KW (932BHP) X 1set  
 Cargo Tanks :  
 (Capacity : M<sup>3</sup>)

	PORT	STBD.
*No.1	1,083.494	1,099.496
*No.2	1,341.025	1,341.030
No.3	1,295.122	1,279.729
*No.4	1,294.109	1,309.110
No.5	1,396.534	1,380.954
*No.6	1,292.449	1,307.832
No.7	1,285.167	1,269.784
*No.8	1,029.969	1,029.964
<b>TOTAL</b>	<b>10,017.869</b>	<b>10,017.899</b>
<b>G.TOTAL</b>	<b>20,035.768</b>	

(Slop tank : 8S)

Material of Cargo Tank : Stainless Steel 316L for all cargo tank  
 Designed Cargo Tank Specific Gravity : 1.5 tons/m<sup>3</sup>  
 Acid Cargo Stowage : 1PS/2PS/4PS/6PS/8PS  
 Submerged Cargo Pump : 300m<sup>3</sup>/h x 0.78MPa x 10 Sets (1,3,4,6,8PS)(CVS-150 : Shaft Carpenter20)  
 : 300m<sup>3</sup>/h x 0.78MPa x 6 Sets (2,5,7PS) (CVS-150 : Shaft SUS316L)  
 Portable cargo Pump : 70m<sup>3</sup>/h x 0.69MPa x 1 Set (Casing/Shaft SUS316L, Impeller SCS16)  
 Cargo Manifold : Common Line Manifold ANSI-10inch Independent Manifold ANSI-6 inch  
 Heating System : All tank (SUS316L Heating Coil) by Steam

Cargo Hose Crane : SWL 5 Ton  
 Single Point Mooring Equipment : 1-Set in forecasble deck (SWL 204MT/ Tongue type)