

# TATSUMI MARINE CO.,LTD.

3RD FLOOR, TATSUMI BLDG.  
 3-8-7 IIDABASHI CHIYODAKU, TOKYO 102-0072, JAPAN  
 Phone : 03-3265-5215/5216/5217 (Business Dept)  
 Fax : 03-3265-5315



## M/T " SOUTHERN VULTURE "

Type : OIL/CHEMICAL TANKER  
 Owner : SANSHO LINE, S.A.  
 Operator : TATSUMI MARINE CO., LTD.  
 Built : 15th APRIL, 2019  
 Builder : ASAKAWA SHIPBUILDING CO., LTD. S-NO : 631  
 Nationality : LIBERIA  
 IMO Number : 9852274  
 Call Sign : D5TJ3  
 Inmarsat FBB Phone : 010-870-7732-02880  
 Inmarsat FBB Fax : 010-870-7830-50216  
 MMSI : 636019191  
 E-Mail : southernvulture@vessel.orcamail.com  
 Inmarsat C E-Mail : 463727585@satmail.com  
 Length (O.A.) : 134.93M  
 Length (B.P.) : 128.00M  
 Breadth : 23.23M  
 Depth : 12.55M  
 Draft : 9.464 M (SUMMER)  
 Dead Weight : 17,402.00 MT  
 Gross Tonnage : 9,995 TONS  
 Net Tonnage : 5,764 TONS  
 Class : Class NK(No.191406) : NS\* (Tanker, Oils-Flashpoint on and below 60°C and Chemicals Type II & III, PSPC-WBT) (ESP)(IWS)(IHM), MNS\*  
 Engine : HITACHI-MAN B&W 6S40ME-B9.5 2cyc. Crosshead type diesel engine  
 4.620 KW X 124min-1 X 1 Set  
 Speed : 14.00 KNOTS  
 Crew : MAX 25 PERSONS  
 Bow thruster : 550KW (737BHP) X 1set  
 Cargo Tanks :  
 (Capacity : M<sup>3</sup>)

|         | PORT              | STBD.            |
|---------|-------------------|------------------|
| *No.1   | 1,053.262         | 1,037.308        |
| *No.2   | 1,355.735         | 1,341.495        |
| No.3    | 1,329.359         | 1,313.531        |
| *No.4   | 1,323.077         | 1,309.018        |
| No.5    | 1,327.261         | 1,314.270        |
| *No.6   | 1,326.900         | 1,313.034        |
| No.7    | 1,343.050         | 1,329.620        |
| *No.8   | 1,046.180         | 1,031.862        |
| TOTAL   | <b>10,104.824</b> | <b>9,990.138</b> |
| G.TOTAL | <b>20,094.962</b> |                  |

(Slop tank : 8S)

Material of Cargo Tank : Stainless Steel 316L for all cargo tank  
 Designed Cargo Tank Specific Grav : 1.5 tons/m<sup>3</sup>  
 Acid Cargo Stowage : 1PS/3PS/4PS/6PS/8PS  
 Submerged Cargo Pump : 300m<sup>3</sup>/h x 0.78MPa x 10 Sets (1, 3, 4, 6, 8 PS) (Carpenter20 / SUS316L)  
 : 300m<sup>3</sup>/h x 0.78MPa x 6 Sets (2, 5, 7 PS) (SUS316L)  
 Portable cargo Pump : 70m<sup>3</sup>/h x 0.69MPa x 1 Set (SUS316)  
 Cargo Manifold : Common Line Manifold ANSI-10inch Independent Manifold ANSI-6 inch  
 Heating System : All tank (SUS316L Heating Coil) by Steam  
 Cargo Hose Crane : SWL 10 Ton  
 Single Point Mooring Equipment : 1-Set in forecastle deck (SWL 204MT/ Tongue type)